


# Datasheet

## Plain/threaded union with o-ring Rp PVC-U



d [mm]	Rp [inch]	d [inch]	PN	EPDM Code	SP	GP	kg	L1 [mm]	L2 [mm]	Z1 [mm]	Z2 [mm]	F [inch]	E [mm]
16	3/8		16	<b>RV0BOP16A</b>	10	250	0.031	14.0	11.4	3.0	13.6	3/4	34
20	1/2		16	<b>RV0BOP20B</b>	10	150	0.042	16.0	15.0	3.0	11.0	1	42
25	3/4		16	<b>RV0BOP25C</b>	10	100	0.070	19.0	16.3	3.0	12.7	1 1/4	52
32	1		16	<b>RV0BOP32D</b>	10	60	0.094	22.0	19.1	3.0	12.9	1 1/2	59
40	1 1/4		16	<b>RV0BOP40E</b>	90	-	0.155	26.0	21.4	3.0	16.6	2	72
50	1 1/2		16	<b>RV0BOP50F</b>	60	-	0.237	31.0	21.4	3.0	23.6	2 1/4	79
63	2		16	<b>RV0BOP63G</b>	36	-	0.382	38.0	25.7	3.0	30.3	2 3/4	96
75	2 1/2	2 1/2	16	<b>RV0BOP75H</b>	20	-	0.625	44.0	30.2	3.0	31.8	3 1/2	119
90	3		16	<b>RV0BOP90I</b>	15	-	0.865	51.0	33.3	5.0	35.7	4	134
110	4		16	<b>RV0BOP91L</b>	18	-	1.340	61.0	39.3	5.0	39.7	5	163

PF 2 01 951 011