




COOL-FIT 4.0 Installation fitting type 313 Rp d32-d225

Model:


- Pre-insulated, PE100, SDR11, metric
- Insulation made from GF HE foam
- Impact resistant. Color: black
- With threaded branch for sensors (i.e temperature, pressure)
- A: Electrofusion Fitting with integrated sealing lip, for a water and vapour tight sealing
- B: Spigot Fitting with free end



B



A



B

d	D	DN	Thread	Size	PN	Code	Weight	H	L	L1	z	Type
(mm)	(mm)	(mm)		(inch)	(bar)		(kg)	(mm)	(mm)	(mm)	(mm)	
32	90	25	Rp	½	16	738 313 608	0.169	92	79	36	18	A
40	110	32	Rp	½	16	738 313 609	0.267	105	87	40	22	A
40	110	32	Rp	¾	16	738 313 659	0.269	108	87	40	22	A
50	110	40	Rp	½	16	738 313 610	0.354	107	94	44	25	A
50	110	40	Rp	¾	16	738 313 660	0.356	110	94	44	25	A
63	125	50	Rp	½	16	738 313 611	0.537	120	103	48	30	A
63	125	50	Rp	¾	16	738 313 661	0.539	123	103	48	30	A
75	140	65	Rp	½	16	738 313 612	0.773	127	116	55	36	A
75	140	65	Rp	¾	16	738 313 662	0.774	130	116	55	36	A
90	160	80	Rp	½	16	738 313 613	1.164	139	130	62	43	A
90	160	80	Rp	¾	16	738 313 663	1.165	142	130	62	43	A
110	180	100	Rp	½	16	738 313 614	1.944	151	154	72	57	A
110	180	100	Rp	¾	16	738 313 664	1.944	154	154	72	57	A
140	225	125	Rp	½	16	738 313 616	3.974	187	175	84	66	A
140	225	125	Rp	¾	16	738 313 666	3.964	190	175	84	66	A
160	250	150	Rp	½	16	738 313 617	2.496	134	165	90	330	B
160	250	150	Rp	¾	16	738 313 667	2.489	134	165	90	330	B
225	315	200	Rp	½	16	738 313 620	5.155	166	185	110	370	B
225	315	200	Rp	¾	16	738 313 670	5.146	169	185	110	370	B

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>