



PROGEF Standard Ball valve type 180
100-230V
With manual emergency override
With backing flanges PP-St ISO with PP-H

Model:

- IP68 Rating
- Factory set control range 90°<
- Heating element, position feedback (Open/Close/ Middle)
- Integrated stainless steel mounting inserts

Option:

- Other valve and actuator configurations available
- Optional accessories: Monitoring board, Positioner, Profibus DP board, Modbus TCP EA 25-250 Ethernet Interface Card

d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	EPDM Code	Weight (kg)	FKM Code	Weight (kg)
75	65	2 ½	10	5000	199 180 129	10.500	199 180 139	10.500
90	80	3	10	7000	199 180 130	11.520	199 180 140	11.880
110	100	4	10	11000	199 180 131	18.400	199 180 141	18.400

d (mm)	Actuator	b1 (mm)	B3 (mm)	D1 (mm)	DE1 (mm)	E (mm)	G (mm)	H (mm)	H1 (mm)	H4 (mm)	k1 (mm)	L (mm)	L1 (mm)	Lz (mm)	M (mm)
75	EA45	18	70	166	166	122	M8	313	85	15	145	290	33	68	180
90	EA45	20	70	200	200	122	M8	325	105	15	160	310	33	71	180
110	EA120	20	120	238	238	122	M12	363	123	22	180	350	33	82	180

d (mm)	M1 (mm)	M2 (mm)
75	98	82
90	98	82
110	98	82

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>