





PROGEF Standard Diaphragm valve type 604 Unions with butt fusion spigot metric

Model:

- Material: PP-H
- Compact full plastic design without screws
- High flow rate
- Actuator housing with thread for easy maintenance
- Quick opening & closing times
- For easy installation and removal
- Market standard installation length

Option:

- Individual configuration of the valve

* O-Ring material: FKM

d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value ($\Delta p=1$ bar) (L/min)	Actuator	EPDM Code	FKM Code	Weight (kg)
20	15	½	6	125	FC	167 604 112	167 604 162	0.35
20	15	½	6	125	FO	167 604 114	167 604 164	0.32
20	15	½	6	125	DA	167 604 115	167 604 165	0.30

d (mm)	PTFE/ EPDM* Code
20	167 604 132
20	167 604 134
20	167 604 135

d (mm)	D (mm)	D1_G (inch)	D3 (mm)	H (mm)	H1 (mm)	H2 (mm)	H3 (mm)	H4 (mm)	H7 (mm)	L (mm)	L2 (mm)	M	z (mm)	Lift = Hx (mm)
20	65	¼	48	89	14	12	46	30	42	196	25	M6	100	6
20	65	¼	48	89	14	12	46	30	42	196	25	M6	100	6
20	65	¼	48	89	14	12	46	30	42	196	25	M6	100	6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>