


PVC-U Multilayer Sewer Pipe SN4 (SDR 41), Single Socket (KGEM)



Material	PVC-U, multilayer (co-extruded) wall
Standard	SR EN 13476-1,2
Ring stiffness	SN4 (SDR 41)
Colour	Orange (RAL 8023)
Application	Non-pressure underground sewage and rainwater drainage outside buildings
Joining	Socket with EPDM sealing ring (factory-fitted)
Temperature	Max. 60 °C for D 110-200; 40 °C for D 250-500 (60 °C short-term)
Chemical resistance	pH 2 - pH 12
Service life	Minimum 50 years

Code	D (mm)	s (mm)	SN	L (m)	Lm (mm)
V95110032I11000ORB	110	3.2	4	1	60
V95110032I12000ORB	110	3.2	4	2	60
V95110032I13000ORB	110	3.2	4	3	60
V95110032I14000ORB	110	3.2	4	4	60
V95110032I15000ORB	110	3.2	4	5	60
V95110032I16000ORB	110	3.2	4	6	60
V95125032I11000ORB	125	3.2	4	1	67
V95125032I12000ORB	125	3.2	4	2	67
V95125032I13000ORB	125	3.2	4	3	67
V95125032I14000ORB	125	3.2	4	4	67
V95125032I15000ORB	125	3.2	4	5	67
V95125032I16000ORB	125	3.2	4	6	67
V95160040I11000ORB	160	4.0	4	1	81
V95160040I12000ORB	160	4.0	4	2	81
V95160040I13000ORB	160	4.0	4	3	81
V95160040I14000ORB	160	4.0	4	4	81
V95160040I15000ORB	160	4.0	4	5	81
V95160040I16000ORB	160	4.0	4	6	81
V95200049I11000ORB	200	4.9	4	1	99
V95200049I12000ORB	200	4.9	4	2	99
V95200049I13000ORB	200	4.9	4	3	99
V95200049I14000ORB	200	4.9	4	4	99
V95200049I15000ORB	200	4.9	4	5	99
V95200049I16000ORB	200	4.9	4	6	99

Code	D (mm)	s (mm)	SN	L (m)	Lm (mm)
V95250062I11000ORB	250	6.2	4	1	125
V95250062I12000ORB	250	6.2	4	2	125
V95250062I13000ORB	250	6.2	4	3	125
V95250062I14000ORB	250	6.2	4	4	125
V95250062I15000ORB	250	6.2	4	5	125
V95250062I16000ORB	250	6.2	4	6	125
V95315077I11000ORB	315	7.7	4	1	132
V95315077I12000ORB	315	7.7	4	2	132
V95315077I13000ORB	315	7.7	4	3	132
V95315077I14000ORB	315	7.7	4	4	132
V95315077I15000ORB	315	7.7	4	5	132
V95315077I16000ORB	315	7.7	4	6	132
V95400098I11000ORB	400	9.8	4	1	150
V95400098I12000ORB	400	9.8	4	2	150
V95400098I13000ORB	400	9.8	4	3	150
V95400098I14000ORB	400	9.8	4	4	150
V95400098I15000ORB	400	9.8	4	5	150
V95400098I16000ORB	400	9.8	4	6	150
V95500123I11000ORB	500	12.3	4	1	160
V95500123I12000ORB	500	12.3	4	2	160
V95500123I13000ORB	500	12.3	4	3	160
V95500123I14000ORB	500	12.3	4	4	160
V95500123I15000ORB	500	12.3	4	5	160
V95500123I16000ORB	500	12.3	4	6	160

Dimensions as published by the manufacturer; symbols refer to the drawing above.

On order we can deliver SN4 pipes 4m and 6m length with glued socket.