



Elbow 45° ABS metric / BS

- >d225 - maximum operating temperature: +40°C

d (mm)	d (inch)	Size (inch)	PN (bar)	Code	SP	Weight (kg)	D (mm)	L (mm)	z (mm)	closest inch (inch)
20			16	729 150 106	10	0.009	25	21	5	½
25			16	729 150 107	10	0.013	31	25	6	¾
32			10	729 150 108	10	0.026	40	30	8	1
40			10	729 150 109	10	0.044	49	36	10	1 ¼
50			10	729 150 110	5	0.079	61	43	12	1 ½
63			10	729 150 111	10	0.143	76	52	14	2
* 75	2 ½	2 ½	10	729 150 112	5	0.225	89	61	17	2 ½
90			10	729 150 113	4	0.363	107	71	20	3
110			10	729 150 114	10	0.567	131	89	28	4
* 140	5	5	10	729 150 116	1	1.175	162	108	32	5
160			10	729 150 117	4	1.713	185	122	36	6
200			10	729 150 119	1	2.546	225	149	43	8
225			10	729 150 120	1	3.162	250	168	49	8
		½	15	729 151 106	10	0.010	28	24	7	
		¾	15	729 151 107	10	0.015	33	29	8	
		1	15	729 151 108	10	0.027	41	33	10	
		1 ¼	15	729 151 109	10	0.046	51	40	11	
		1 ½	15	729 151 110	5	0.068	57	41	11	
		2	15	729 151 111	10	0.134	72	51	15	
		3	15	729 151 113	5	0.407	109	72	21	
		4	15	729 151 115	5	0.714	135	89	26	

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>