




PROGEF Standard Ball valve type 127
24V
With manual emergency override
With fusion sockets PP-H ISO

Model:


- Factory set control range 90°<
- Heating element, position feedback (Open/Close)
- Integrated stainless steel mounting inserts
- IP68 Rating

Option:


- Other valve and actuator configurations available
- Optional accessories: Fail-safe return unit



d	DN	Size	PN	kv-value	EPDM	Weight	FKM	Weight
(mm)	(mm)	(inch)	(bar)	($\Delta p=1$ bar)	Code	(kg)	Code	(kg)
				(l/min)				
16	10	3/8	10	70	199 127 542	2.100	199 127 552	2.100
20	15	1/2	10	185	199 127 543	2.100	199 127 553	2.100
25	20	3/4	10	350	199 127 544	2.167	199 127 554	2.200
32	25	1	10	700	199 127 545	2.300	199 127 555	2.241
40	32	1 1/4	10	1000	199 127 546	2.418	199 127 556	2.600
50	40	1 1/2	10	1600	199 127 547	3.000	199 127 557	3.000
63	50	2	10	3100	199 127 548	3.800	199 127 558	3.800



d	Actuator	B3	DE1	E	G	H	H1	H4	L	L1	Lz	M	M1	M2	z
(mm)		(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
16	EA15	25	50	122	M6	197	27	12	93	33	28	161	77	83	67
20	EA15	25	50	122	M6	197	27	12	95	33	28	161	77	83	66
25	EA15	25	58	122	M6	201	30	12	109	33	33	161	77	83	77
32	EA15	25	68	122	M6	207	36	12	119	33	36	161	77	83	83
40	EA15	45	84	122	M8	213	44	15	135	33	43	161	77	83	99
50	EA15	45	97	122	M8	219	51	15	147	33	45	161	77	83	105
63	EA15	45	124	122	M8	234	64	15	168	33	51	161	77	83	117



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>