



Installation fitting type 310 ABS metric

Model:

- Threaded outlet 1 1/4" NPSM
- With solvent cement socket metric
- Material: ABS

Range of use:

- Compatible Signet pH/ORP sensors: type 2724, 2725, 2726, 2734, 2736, 2735
- Compatible Signet flow sensors: type 2551, 2537, 515, 8510, 2536, 8512

Attention:

- sensor length depends on installation fitting

d (mm)	DN (mm)	PN (bar)	Code	SP	Weight (kg)	z (mm)	Sensor Type	D (mm)	H (mm)	L (mm)
25	20	10	729 310 007	1	0.100	32	X0 (DN15 – DN100, 1/2" to 4")	35	78	100
32	25	10	729 310 008	1	0.143	33	X0 (DN15 – DN100, 1/2" to 4")	44	81	110
40	32	10	729 310 009	1	0.140	29	X0 (DN15 – DN100, 1/2" to 4")	51	84	110
50	40	10	729 310 010	1	0.187	29	X0 (DN15 – DN100, 1/2" to 4")	63	88	120
63	50	10	729 310 011	1	0.257	28	X0 (DN15 – DN100, 1/2" to 4")	78	94	130

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>