Data sheet

valid from: 3/28/26



SYGEF Standard Pressure retaining valve type 586
Unions with fusion sockets metric
Without manometer

Model:

- Diaphragm PTFE/EPDM
- Integrated stainless steel mounting inserts
- 0.5-9.0 bar (7-130 psi)

0.3-3.0 bar (4-44 psi) on request
Manometer on request



d (mm)	DN (mm)	Size (inch)	PN (bar)	O-rings FKM Code	SP	Weight (kg)
20	15	½	10	**185 586 112**	1	0.780
25	20	¾	10	**185 586 113**	1	1.670
32	25	1	10	**185 586 114**	1	1.720
40	32	1 ¼	10	**185 586 115**	1	4.700
50	40	1 ½	10	**185 586 116**	1	4.790
63	50	2	10	**185 586 117**	1	5.090

d (mm)	D (mm)	H (mm)	H1 (mm)	H2 (mm)	H3 (mm)	L (mm)	L2 (mm)	L3 (mm)	M	z (mm)	closest inch (inch)
20	79	132	111	21	12	158	120	42	M6	130	½
25	100	177	148	29	14	192	150	53	M6	160	¾
32	100	177	148	29	14	196	150	53	M6	160	1
40	147	251	207	44	21	255	205	76	M8	215	1 ¼
50	147	251	207	44	21	261	205	76	M8	215	1 ½
63	147	251	207	44	21	269	205	76	M8	215	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com