



Wafer-style intermediate installation butterfly valve type 565 PE
With pneumatic actuator - double acting (DA)
Flange standard ISO/Metric
Suitable for ABS, PVC-U, PVC-C, ecoFIT, COOL-FIT and PROGEF Systems

Model:




- Installation length: EN558 row 20, ISO 5752 row 20, API 609 table 2
- Flange standards: ISO 7005 PN10, EN 1092 PN10, DIN 2501 PN10
- For easy installation and removal
- Control time 0-90° 5-6s
- Control pressure 5.6 bar
- Suitable for water and water treatment applications (e.g. sea water, drinking water and industrial water)

Option:

- Individual configuration of the valve possible
- Double sensor for electrical position feedback incl. LED feedback
- Gear box or electric actuators

Note:

For some material combination (e.g. valves with PE/PP pipes) special flange adapters are needed. Please check the "Perfect flange connection tool" on www.gfps.com



d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value ($\Delta p=1$ bar) (L/min)	Acc.to ISO 5211	EPDM Code	Weight (kg)
355	350	14	10	148808	F14	199 555 600	50.600
400	400	16	10	185266	F14	199 555 601	72.900

d (mm)	DN (mm)	d2 (mm)	U (mm)	V (mm)	H4 (mm)	Hmax (mm)	V1 (mm)	Y (mm)	Q2 (mm)	Lg (mm)	Lmax (mm)	D2 (mm)	k (mm)	M1 (mm)	M2 (mm)
355	350	22	180	332	29	820	290	198	331	78	479.4	517	460	239.7	239.7
400	400	26	180	367	29	912	329	216	379	102	567.1	579	515	283.6	283.6

d (mm)	DN (mm)	E (mm)	Wmax (mm)	d2
355	350	168	530.0	M20
400	400	186	590.5	M24

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>