




PROGEF Standard Ball valve type 127
24V
With manual emergency override
With fixed flanges PP-H ser. ISO

Model:

- IP68 Rating
- Factory set control range 90°<
- Heating element, position feedback (Open/Close)
- Integrated stainless steel mounting inserts

Option:

- Other valve and actuator configurations available
- Optional accessories: Fail-safe return unit



d	DN	Size	PN	kv-value	EPDM	Weight
(mm)	(mm)	(inch)	(bar)	($\Delta p=1$ bar)	Code	(kg)
				(l/min)		
20	15	½	10	185	199 127 783	2.300
25	20	¾	10	350	199 127 784	2.500
32	25	1	10	700	199 127 785	2.700
40	32	1 ¼	10	1000	199 127 786	2.496
50	40	1 ½	10	1600	199 127 787	3.700
63	50	2	10	3100	199 127 788	4.800

d	Actuator	b1	B3	D1	DE1	E	G	H	H1	H4	k1	L	L1	Lz	M
(mm)		(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
20	EA15	12	25	95	50	122	M6	197	27	12	56	120	33	28	161
25	EA15	12	25	105	58	122	M6	201	30	12	75	139	33	33	161
32	EA15	14	25	115	68	122	M6	207	36	12	85	150	33	36	161
40	EA15	16	45	140	84	122	M8	213	44	15	100	170	33	43	161
50	EA15	16	45	150	97	122	M8	219	51	15	110	189	33	45	161
63	EA15	18	45	165	124	122	M8	234	64	15	125	219	33	51	161

d	M1	M2
(mm)	(mm)	(mm)
20	77	83
25	77	83
32	77	83
40	77	83
50	77	83
63	77	83

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>