


ELGEF Plus Elbow 45° PE100 d32-63mm / SDR11 / with integral pipe fixation

- 10 bar Gas / 16 bar Water
- 4 mm pin connectors
- Limited path fusion indicators

d	DN	PN	SDR	Code	Weight	d1	L	L1	z	SDR pipe
(mm)	(mm)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)	
32	25	16	11	753 151 608	0.075	44	44	36	8	9-11
40	32	16	11	753 151 609	0.106	54	50	39	11	9-11
50	40	16	11	753 151 610	0.171	66	56	43	13	9-11
63	50	16	11	753 151 611	0.252	81	63	48	15	9-17.6




ELGEF Plus Elbow 45° PE100 d75-180mm / SDR11

- 10 bar Gas / 16 bar Water
- 4 mm pin connectors
- Limited path fusion indicators



d	DN	PN	SDR	Code	Weight	d1	L	L1	z	SDR pipe
(mm)	(mm)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)	
75	65	16	11	753 151 612	0.332	97	71	54	17	9-11
90	80	16	11	753 151 813	0.583	115	91	62	29	9-11
110	100	16	11	753 151 814	0.985	140	112	72	40	9-17.6
125	100	16	11	753 151 815	1.438	160	119	78	49	9-17.6
140	125	16	11	753 151 816	2.242	185	125	83	42	9-17.6
160	150	16	11	753 151 817	3.055	196	135	92	42	11-17.6
180	150	16	11	753 151 818	4.037	217	144	95	47	11-17.6



ELGEF Plus Elbow 45° PE100 d200-250mm / SDR11

- 10 bar Gas / 16 bar Water
- 4 mm pin connectors
- Limited path fusion indicators
- Two separate fusion zones

d	DN	PN	SDR	Code	Weight	d1	L	L1	z	SDR pipe
(mm)	(mm)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)	
200	200	16	11	753 151 819	7.566	250	232	104	128	11-26
225	200	16	11	753 151 820	11.300	280	247	112	135	11-26
250	250	16	11	753 151 821	13.500	310	275	123	152	11-26