




**ecoFIT Reducing bush metric PE100**  
**d20-50mm / SDR11 / Female thread Rp**

**Model:**

- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Do not use thread sealing pastes that are harmful to PE
- Install with low mechanical stress and avoid large cyclic temperature changes
- With fusion spigot metric and BSP parallel female thread, reinforced



| d<br>(mm) | Thread Type | Size<br>(inch) | DN<br>(mm) | SDR | PN<br>(bar) | Code               | Weight<br>(kg) | Do<br>(mm) | Lmax<br>(mm) | z<br>(mm) |
|-----------|-------------|----------------|------------|-----|-------------|--------------------|----------------|------------|--------------|-----------|
| 20        | Rp          | 3/8            | 15         | 11  | 10          | <b>733 910 434</b> | 0.012          | 26         | 33           | 7         |
| 25        | Rp          | 1/2            | 20         | 11  | 10          | <b>733 910 437</b> | 0.015          | 31         | 37           | 6         |
| 32        | Rp          | 3/4            | 25         | 11  | 10          | <b>733 910 441</b> | 0.028          | 36         | 43           | 8         |
| 40        | Rp          | 1              | 32         | 11  | 10          | <b>733 910 446</b> | 0.046          | 45         | 49           | 9         |
| 50        | Rp          | 1 1/4          | 40         | 11  | 10          | <b>733 910 452</b> | 0.071          | 55         | 55           | 10        |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:  
info.ps@georgfischer.com Internet: <http://www.gfps.com>