



Installation fitting type 312 ABS metric

Model:

- Saddle with threaded outlet 1 1/4" NPSM
- Top saddle for solvent cement bonding
- Material: ABS

Range of use:

- Compatible Signet flow sensors: type 2551, 2537, 515, 8510, 2536, 8512

Attention:

- sensor length depends on installation fitting

d	DN	PN	Code	SP	Weight	D	H	Sensor Type
(mm)	(mm)	(bar)			(kg)	(mm)	(mm)	
75	65	10	729 312 012	1	0.170	38	91	X1 (DN125 - DN200, 5" to 8")
90	80	10	729 312 013	1	0.176	38	91	X1 (DN125 - DN200, 5" to 8")
110	100	10	729 312 014	1	0.172	38	91	X1 (DN125 - DN200, 5" to 8")
140	125	10	729 312 016	1	0.166	38	81	X1 (DN125 - DN200, 5" to 8")
160	150	10	729 312 017	1	0.166	38	77	X1 (DN125 - DN200, 5" to 8")
200	200	10	729 312 019	1	0.152	38	71	X1 (DN125 - DN200, 5" to 8")
225	200	10	729 312 020	1	0.196	38	67	X1 (DN125 - DN200, 5" to 8")

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>