



COOL-FIT 2.0 Sliding coupler kit

Model:

- Pre-insulated PE100 SDR11 metric
- Insulation made from GF HE foam
- Outer jacket impact resistant. Color: black
- Integrated sealing lip, for a moisture-proof and vapour tight sealing
- Including two couplers, pipe section and four insulation half shells

d	D	DN	PN	Code	Weight	Dos	Lmax	P1	P2	z
(mm)	(mm)	(mm)	(bar)		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
32	75	25	16	738 914 508	0.311	82	376	36	36	268
40	90	32	16	738 914 509	0.446	97	402	40	40	284
50	90	40	16	738 914 510	0.589	97	422	44	44	296
63	110	50	16	738 914 511	0.907	117	452	48	48	318
75	125	65	16	738 914 512	1.309	133	493	55	55	344
90	140	80	16	738 914 513	1.890	148	532	62	62	370
110	160	100	16	738 914 514	3.078	168	604	72	72	420
140	200	125	16	738 914 516	4.851	208	673	84	84	466

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>