



Wafer-Style, intermediate installation butterfly valve metal type 039
With pneumatic actuator - fail safe to close(FC) - Actuator CN
Flange standard Metric/Inch/ASTM - PN10
Disc: ductile iron/Rilsan® coated

Model:

- Wafer Style
- Body GGG40 (A 395 / A395 M-99, EN-JIS 1020 EN1563) Rilsan® coating
- Installation length: EN 558 row 20
- Interface according to DIN EN ISO 5211
- Pressure range: 10 bar (DN 50-200); 6 bar (DN 250); 4 bar (DN 300 - 600)
- Axis DN50 - DN300: Single-piece axis with square profile, material stainless steel DIN Norm 1.4021
- Flange connection: DN50 - DN300: PN6, PN10, ANSI 125/150 Lbs., BS 10-D/E

Option:

- Other liner material on request

d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value (Δp=1 bar) (l/min)	Liner: EPDM Code	SP	Weight (kg)
63	50	2	10	3167	199 039 290	1	0.00
75	65	2 ½	10	4667	199 039 291	1	6.10
90	80	3	10	7167	199 039 292	1	6.40
110	100	4	10	11833	199 039 293	1	8.80
140	125	5	10	18333	199 039 294	1	10.50
160	150	6	10	26667	199 039 295	1	16.00
225	200	8	10	46667	199 039 296	1	5.32
280	250	10	6	78333	199 039 297	1	6.02
315	300	12	4	115000	199 039 298	1	6.97

d (mm)	Liner: FKM Code	Liner: EPDM DVGW Code	Liner: NBR Code	PF
63	199 039 521	199 039 710	199 039 391	3 39 226 267
75	199 039 522	199 039 711	199 039 392	3 39 226 267
90	199 039 523	199 039 712	199 039 393	3 39 226 267
110	199 039 524	199 039 713	199 039 394	3 39 226 267
140	199 039 525	199 039 714	199 039 395	3 39 226 267
160	199 039 526	199 039 715	199 039 396	3 39 226 267
225	199 039 527	199 039 716	199 039 397	3 39 226 267
280	199 039 528	199 039 717	199 039 398	3 39 226 267
315	199 039 529	199 039 718	199 039 399	3 39 226 267

d (mm)	Type of actuator	H (mm)	H1 (mm)	H2 (mm)	H3 (mm)	L1 (mm)	L3 (mm)	Q (mm)
63	CN63	341	83	140	118	152	82	32
75	CN63	363	93	152	118	152	82	51
90	CN63	375	98	159	118	152	82	69
110	CN75	409	111	178	120	202	94	89
140	CN75	438	127	191	120	202	94	115
160	CN105	491	143	203	145	271	122	143
225	CN105	562	172	241	145	271	122	194
280	CN125	662	204	275	185	360	137	243
315	CN140	803	242	315	246	360	153	293

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Data sheet

valid from: 3/2/26



Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>