



Wafer-style intermediate installation butterfly valve type 565 PE

With gear box

Flange standard ISO/Metric

Suitable for ABS, PVC-U, PVC-C, ecoFIT, COOL-FIT and PROGEF Systems

Model:




- Installation length: EN558 row 20, ISO 5752 row 20, API 609 table 2
- Flange standards: ISO 7005 PN10, EN 1092 PN10, DIN 2501 PN10
- For easy installation and removal
- Suitable for water and water treatment applications (e.g. sea water, drinking water and industrial water)

Option:

- Individual configuration of the valve possible
- Double sensor for electrical position feedback incl. LED feedback
- Pneumatic or electric actuators

Note:

For some material combination (e.g. valves with PE/PP pipes) special flange adapters are needed. Please check the "Perfect flange connection tool" on www.gfps.com



d	Size	DN	PN	Acc.to ISO	kv-value	EPDM	Weight
(mm)	(inch)	(mm)	(bar)	5211	(Δp=1 bar)	Code	(kg)
355	14	350	10	F14	148808	199 555 200	49.500
400	16	400	10	F14	185266	199 555 201	65.700

d	d2	M	U	V	H4	Hmax	V1	Y	LV	Q2	Lg	Lmax	LB	H	D2
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
355	22	500	200	332	29	668.5	290	93	242	331	78	500	114	374	517
400	26	500	200	367	29	742.5	329	93	242	379	102	500	114	409	579

d	k	E	Wmax	d2	ba1	ta1	ha1
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
355	460	200	569	M20	12	5	8
400	515	200	600	M24	12	5	8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>