


PVC Elbow SN4, Single Socket (KGB)



Material	PVC-U
Ring stiffness	SN4 (also used with SN2 pipes)
Colour	Orange (RAL 8023)
Application	Non-pressure underground sewage and rainwater drainage outside buildings
Jointing	Socket with EPDM sealing ring
Temperature	Max. 60 °C for D 110–200; 40 °C for D 250–500 (60 °C short-term)

Code	D (mm)	α (°)	SN	Z1 (mm)	Z2 (mm)
FVE0188*	110	15	4	9	15
FVE0197	125	15	4	10	16
FVE0191	160	15	4	13	19
FVE0201	200	15	4	15	25
FVE0202	250	15	4	28	34
FVE0192	315	15	4	35	42
FVE0294	400	15	4	34	53
FVE0309	500	15	4	150	160
FVE0169	110	30	4	17	22
FVE0190	125	30	4	19	23
FVE0168	160	30	4	24	30
FVE0255	200	30	4	30	38
FVE0203	250	30	4	46	50
FVE0222	315	30	4	59	62
MFD0370	400	30	4	64	83
FVE0310	500	30	4	165	230
FPVCT110XXX45IOR	110	45	4	19	36
FVE0076	125	45	4	28	33

Code	D (mm)	α (°)	SN	Z1 (mm)	Z2 (mm)
FPVCT160XXX45IOR	160	45	4	33	45
FVE0034	200	45	4	46	54
FVE0014	250	45	4	66	69
FVE0056	315	45	4	84	86
FVE0052	400	45	4	96	110
MFD0368	500	45	4	103	152
FVE0010	110	67	4	41	47
FVE0138	125	67	4	46	50
FVE0131	160	67	4	59	65
FVE0108	200	67	4	73	82
FVE0011	110	87	4	59	65
FVE0077	125	87	4	65	70
FVE0001	160	87	4	83	89
FVE0013	200	87	4	105	113
FVE0002	250	87	4	141	143
FVE0046	315	87	4	178	180
FVE0047	400	87	4	216	229
FVE0195	500	87	4	380	430

Dimensions as published by the manufacturer; symbols refer to the drawing above.