






**Wafer-style intermediate installation butterfly valve type 567 ABS**  
**With gear box**  
**Flange standard metric/ANSI/BS/JIS**

**Model:**

- Overall length according to EN 558, ISO 5752
- Connecting dimension: ISO 7005 PN 10, EN 1092 PN 10, DIN 2501 PN 10, ANSI/ASME B 16.5 Class 150, BS 1560: 1989, BS 4504, JIS B 2220

**Note:**

For some material combination (e.g. DN300 valves with PE/PP pipes) special flange adapters are needed. Please check the "Perfect flange connection tool" on [www.gfps.com](http://www.gfps.com)

| d    | Size   | DN   | PN    | kv-value            | EPDM        | Weight |
|------|--------|------|-------|---------------------|-------------|--------|
| (mm) | (inch) | (mm) | (bar) | ( $\Delta p=1$ bar) | Code        | (kg)   |
|      |        |      |       | (l/min)             |             |        |
| 63   | 2      | 50   | 10    | 740                 | 169 567 022 | 3.078  |
| 75   | 2 ½    | 65   | 10    | 1500                | 169 567 023 | 3.201  |
| 90   | 3      | 80   | 10    | 2400                | 169 567 024 | 3.259  |
| 110  | 4      | 100  | 10    | 3800                | 169 567 025 | 3.493  |
| 140  | 5      | 125  | 10    | 8600                | 169 567 026 | 4.526  |
| 160  | 6      | 150  | 10    | 11400               | 169 567 027 | 5.118  |
| 225  | 8      | 200  | 10    | 19900               | 169 567 028 | 6.389  |
| 280  | 10     | 250  | 10    | 34000               | 169 567 029 | 12.998 |
| 315  | 12     | 300  | 10    | 50000               | 169 567 030 | 19.139 |

| d    | Hmax  | Lmax  | Wmax  | U    | V     | H4   | V1    | Lg   | D2   | Q1   | Q2   | Y    | E    | Y1   |
|------|-------|-------|-------|------|-------|------|-------|------|------|------|------|------|------|------|
| (mm) | (mm)  | (mm)  | (mm)  | (mm) | (mm)  | (mm) | (mm)  | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) |
| 63   | 319.4 | 169.1 | 240.2 | 90   | 133.3 | 23   | 78.8  | 45   | 104  | 40   |      | 61.2 | 80   |      |
| 75   | 332.3 | 169.1 | 247.3 | 90   | 139.9 | 23   | 85.1  | 46   | 115  | 54   | 35   | 61.2 | 80   |      |
| 90   | 344.1 | 169.1 | 249.4 | 90   | 145.6 | 23   | 91.2  | 49   | 131  | 67   | 50   | 61.2 | 80   |      |
| 110  | 379.4 | 169.1 | 261.5 | 90   | 166.4 | 23   | 105.7 | 56   | 161  | 88   | 74   | 61.2 | 80   |      |
| 140  | 406.1 | 169.1 | 274.5 | 90   | 180.0 | 23   | 118.8 | 64   | 187  | 113  | 97   | 61.2 | 80   |      |
| 160  | 427.2 | 169.1 | 288.5 | 90   | 189.0 | 23   | 130.9 | 72   | 215  | 139  | 123  | 61.2 | 80   |      |
| 225  | 476.1 | 169.1 | 267.0 | 90   | 210.5 | 23   | 158.3 | 73   | 267  | 178  | 169  | 61.2 | 80   |      |
| 280  | 613.0 | 212.6 | 329.0 | 125  | 262.6 | 23   | 206.1 | 113  | 329  | 210  | 207  | 68.4 | 100  | 17.0 |
| 315  | 657.4 | 212.6 | 380.4 | 125  | 284.3 | 23   | 228.8 | 113  | 379  | 256  | 253  | 68.4 | 100  | 17.0 |

| d    | M    | LV    | LB    |
|------|------|-------|-------|
| (mm) | (mm) | (mm)  | (mm)  |
| 63   | 160  | 112.3 | 129.5 |
| 75   | 160  | 112.3 | 129.5 |
| 90   | 160  | 112.3 | 129.5 |
| 110  | 160  | 112.3 | 129.5 |
| 140  | 160  | 112.3 | 129.5 |
| 160  | 160  | 112.3 | 129.5 |
| 225  | 160  | 112.3 | 129.5 |
| 280  | 200  | 130.0 | 134.0 |
| 315  | 200  | 130.0 | 134.0 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com) Internet: <http://www.gfps.com>