



COOL-FIT 4.0 Sliding coupler kit d32-d225

Model:

- For easy and stress-free integration of pre-assembled components on site
- Pre-insulated PE100 SDR11 metric
- Insulation made from GF HE foam
- Outer jacket impact resistant. Color: black
- Integrated sealing lip, for a moisture-proof and vapour tight sealing
- Including two couplers, pipe section and four insulation half shells

d	D	DN	PN	Code	Weight	Dos	Lmax	P1	P2	z
(mm)	(mm)	(mm)	(bar)		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
32	90	25	16	738 913 508	0.499	97	390	36.0	36	268
40	110	32	16	738 913 509	0.475	117	414	40.0	40	284
50	110	40	16	738 913 510	0.630	117	434	44.0	44	296
63	125	50	16	738 913 511	0.937	132	464	48.0	48	318
75	140	65	16	738 913 512	1.693	147	504	55.0	55	344
90	160	80	16	738 913 513	2.527	168	544	62.0	62	370
110	180	100	16	738 913 514	3.298	188	614	72.0	72	420
140	225	125	16	738 913 516	5.053	234	684	84.0	84	466
160	250	150	16	738 913 517	7.225	258	714	90.0	90	484
225	315	200	16	738 913 520	16.276	324	853	110.0	110	583

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>