



PROGEF Standard Ball valve type 546 Pro
With butt fusion spigots long PP-H SDR11 ISO

Model:

- Lockable lever as standard
- Ball seat PTFE
- Integrated stainless steel mounting inserts
- Z-dimension, valve end and union nut **are compatible** with type 546 (1st Generation)

Option:

- Interface module for position feedback sensor with LED (PNP, NPN and NAMUR)
- Manual spring return lever "Dead man" (DN10-25)
- Pneumatic or electric actuators from GF
- Individual configuration of the valve possible



d	DN	Size	PN	kv-value	EPDM	SP	Weight	FKM	SP	Weight
(mm)	(mm)	(inch)	(bar)	($\Delta p=1$ bar)	Code		(kg)	Code		(kg)
				(l/min)						
20	15	½	10	185	167 546 262	1	0.130	167 546 272	1	0.130
25	20	¾	10	350	167 546 263	1	0.195	167 546 273	1	0.195
32	25	1	10	700	167 546 264	1	0.280	167 546 274	1	0.280
40	32	1 ¼	10	1000	167 546 265	1	0.492	167 546 275	1	0.480
50	40	1 ½	10	1600	167 546 266	1	0.691	167 546 276	1	0.700
63	50	2	10	3100	167 546 267	1	1.274	167 546 277	1	1.288

d	B3	DE1	G	H	H1	H4	L	Lz	M	M1	M2	s1
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
20	25	50	M6	60.5	27	12	193	28	82	35	47	1.9
25	25	58	M6	74.0	30	12	216	33	106	44	62	2.3
32	25	68	M6	80.0	36	12	223	36	106	44	62	3.0
40	45	81	M8	95.0	44	15	249	43	131	57	74	3.7
50	45	97	M8	101.5	51	15	271	45	131	57	74	4.6
63	45	124	M8	116.5	64	15	321	51	152	66	86	5.8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>