


PVC-U Multilayer Sewer Pipe SN2 (SDR 51), Single Socket (KGEM)



Material	PVC-U, multilayer (co-extruded) wall
Standard	SR EN 13476-1,2
Ring stiffness	SN2 (SDR 51)
Colour	Orange (RAL 8023)
Application	Non-pressure underground sewage and rainwater drainage outside buildings
Joining	Socket with EPDM sealing ring (factory-fitted)
Temperature	Max. 60 °C for D 110-200; 40 °C for D 250-500 (60 °C short-term)
Chemical resistance	pH 2 - pH 12
Service life	Minimum 50 years

Code	D (mm)	s (mm)	SN	L tot. (L+Lm, m)	Lm (mm)
V93110022I11000OR	110	2.2	2	1	60
V93110022I12000OR	110	2.2	2	2	60
V93110022I13000OR	110	2.2	2	3	60
V93110022I14000OR	110	2.2	2	4	60
V93110022I16000OR	110	2.2	2	6	60
V93125025I11000OR	125	2.5	2	1	67
V93125025I12000OR	125	2.5	2	2	67
V93125025I13000OR	125	2.5	2	3	67
V93125025I14000OR	125	2.5	2	4	67
V93125025I16000OR	125	2.5	2	6	67
V93160032I11000OR	160	3.2	2	1	81
V93160032I12000OR	160	3.2	2	2	81
V93160032I13000OR	160	3.2	2	3	81
V93160032I14000OR	160	3.2	2	4	81
V93160032I16000OR	160	3.2	2	6	81
V93200039I11000OR	200	3.9	2	1	99
V93200039I12000OR	200	3.9	2	2	99
V93200039I13000OR	200	3.9	2	3	99
V93200039I14000OR	200	3.9	2	4	99
V93200039I16000OR	200	3.9	2	6	99

Code	D (mm)	s (mm)	SN	L tot. (L+Lm, m)	Lm (mm)
V93250049I11000OR	250	4.9	2	1	125
V93250049I12000OR	250	4.9	2	2	125
V93250049I13000OR	250	4.9	2	3	125
V93250049I14000OR	250	4.9	2	4	125
V93250049I16000OR	250	4.9	2	6	125
V93315062I11000OR	315	6.2	2	1	132
V93315062I12000OR	315	6.2	2	2	132
V93315062I13000OR	315	6.2	2	3	132
V93315062I14000OR	315	6.2	2	4	132
V93315062I16000OR	315	6.2	2	6	132
V93400079I11000OR	400	7.9	2	1	150
V93400079I12000OR	400	7.9	2	2	150
V93400079I13000OR	400	7.9	2	3	150
V93400079I14000OR	400	7.9	2	4	150
V93400079I16000OR	400	7.9	2	6	150
V93500098I11000ORB	500	9.8	2	1	160
V93500098I12000ORB	500	9.8	2	2	160
V93500098I13000ORB	500	9.8	2	3	160
V93500098I14000ORB	500	9.8	2	4	160
V93500098I16000ORB	500	9.8	2	6	160

Dimensions as published by the manufacturer; symbols refer to the drawing above.

On request we can deliver SN2 pipes - 5m length. On order we can deliver SN2 pipes 4m and 6m length with glued socket.