



Reducer PVC-U Threaded G/G

d (inch)	d1 (inch)	PN (bar)	Code	SP	GP	Weight (kg)	O (mm)	Z (mm)	L1 (mm)	L2 (mm)	E (mm)
3/8	1/2	16	RV0RIF20A	10	400	0.012	24	24	15.0	11.4	32
3/8	3/4	16	RV0RIF25A	10	280	0.016	30	25	16.3	11.4	23
1/2	3/4	16	RV0RIF25B	10	280	0.018	30	26	16.3	15.0	28
3/8	1	16	RV0RIF32A	10	160	0.024	36	28	19.1	11.4	23
1/2	1	16	RV0RIF32B	10	160	0.025	36	29	19.1	15.0	28
3/4	1	16	RV0RIF32C	10	160	0.026	36	30	19.1	16.3	34
1/2	1 1/4	16	RV0RIF40B	1	150	0.041	46	33	21.4	15.0	28
3/4	1 1/4	16	RV0RIF40C	1	150	0.044	46	33	21.4	16.3	34
1	1 1/4	16	RV0RIF40D	1	150	0.045	46	33	21.4	19.1	42
3/4	1 1/2	16	RV0RIF50C	1	120	0.047	50	34	21.4	16.3	34
1	1 1/2	16	RV0RIF50D	1	100	0.049	50	34	21.4	19.1	42
1 1/4	1 1/2	16	RV0RIF50E	1	100	0.056	55	34	21.4	21.4	51
1	2	16	RV0RIF63D	1	140	0.084	65	37	25.7	19.1	42
1 1/4	2	16	RV0RIF63E	1	140	0.083	65	37	25.7	21.4	51
1 1/2	2	16	RV0RIF63F	1	130	0.091	65	37	25.7	21.4	58
1 1/4	2 1/2	16	RV0RIF75E	1	170	0.137	80	43	30.2	21.4	51
1 1/2	2 1/2	16	RV0RIF75F	1	170	0.136	80	43	30.2	21.4	58
2	2 1/2	16	RV0RIF75G	1	150	0.140	80	43	30.2	25.7	72
1 1/2	3	16	RV0RIF90F	1	150	0.203	95	47	33.3	21.4	58
2	3	16	RV0RIF90G	1	125	0.206	95	47	33.3	25.7	72
2 1/2	3	16	RV0RIF90H	1	115	0.216	95	47	33.3	30.2	89
2	4	16	RV0RIF91G	1	85	0.325	120	53	39.3	25.7	72
3	4	16	RV0RIF91I	1	60	0.342	120	53	39.3	33.3	103
2 1/2	4	16	RV0RIF91H	1	42	0.331	120	53	39.3	30.2	89

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>