



PROGEF Standard Tee 90° PN10 metric Rp

Model:

- Material: PP-H
- Line, with fusion socket metric
- Branch, with BSP parallel female thread Rp, reinforced
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Do not use thread sealing pastes that are harmful to PP
- Install with low mechanical stress and avoid large cyclic temperature changes

d (mm)	Thread Type	Size (inch)	PN (bar)	Code	GP Weight (kg)	L (mm)	D (mm)	D1 (mm)	z1 (mm)	z2 (mm)
20	Rp	½	10	727 200 206	0.030	28	31	30	14	14
25	Rp	¾	10	727 200 207	0.042	32	36	35	16	16
32	Rp	1	10	727 200 208	0.071	38	44	45	20	20
40	Rp	1 ¼	10	727 200 209	0.107	44	54	55	24	24

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>