






COOL-FIT 4.0 Ball valve type 179 100-230V

Model:

- Material: ABS with spigot PE100 SDR11, metric
- Ball seat PTFE
- Integrated stainless steel mounting inserts
- Voltage 100-230V, 50-60Hz
- Factory set control range 90°
- Heating element, position feedback (Open/Close/ Middle)
- Including insulation half shells
- Separate Fittings type A needed for joining



d	DN	PN	Code	Weight
(mm)	(mm)	(bar)		(kg)
32	25	10	138 546 208	2.838
40	32	10	138 546 209	3.174
50	40	10	138 546 210	3.452
63	50	10	138 546 211	4.475
75	65	10	138 546 212	7.156
90	80	10	138 546 213	13.000

d	D	D1	D2	H	H1	H2	L	L1	L3	L4	M	z	z1	z2
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		(mm)	(mm)	(mm)
32	135	97	82	228	36	12	152	36	190	25	M6	223	76	71
40	157	117	97	240	44	15	170	40	190	45	M8	249	82	85
50	169	117	97	246	51	15	184	44	190	45	M8	271	91	89
63	204	132	117	263	64	15	227	48	190	45	M8	321	110	101
75	235	147	132	322	85	15	276	55	190	70	M8	386	125	136
90	255	168	147	357	105	15	297	62	190	70	M8	421	140	141

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>