




COOL-FIT 2.0 Installation fitting type 313 Rp

Model:

- Pre-insulated PE100 SDR11 metric
- Insulation made from GF HE foam
- Impact resistant. Color: black
- With threaded branch for sensors (i.e temperature, pressure)
- A: Electrofusion Fitting with integrated sealing lip, for a moisture-proof and vapour tight sealing



d (mm)	D (mm)	Thread	Size (inch)	DN (mm)	PN (bar)	Code	Weight (kg)	H (mm)	L (mm)	L1 (mm)	z (mm)	Type
32	75	Rp	½	25	16	738 313 408	0.138	75	73	36	16	A
40	90	Rp	½	32	16	738 313 409	0.216	85	81	40	21	A
40	90	Rp	¾	32	16	738 313 459	0.216	88	81	40	21	A
50	90	Rp	½	40	16	738 313 410	0.308	94	88	44	24	A
50	90	Rp	¾	40	16	738 313 460	0.307	97	88	44	24	A
63	110	Rp	½	50	16	738 313 411	0.493	113	97	48	29	A
63	110	Rp	¾	50	16	738 313 461	0.492	116	97	48	29	A
75	125	Rp	½	65	16	738 313 412	0.678	99	110	55	35	A
75	125	Rp	¾	65	16	738 313 462	0.677	102	110	55	35	A
90	140	Rp	½	80	16	738 313 413	1.025	113	123	62	42	A
90	140	Rp	¾	80	16	738 313 463	1.023	116	123	62	42	A
110	160	Rp	½	100	16	738 313 414	1.765	128	148	72	56	A
110	160	Rp	¾	100	16	738 313 464	1.763	131	148	72	56	A
140	200	Rp	½	125	16	738 313 436	3.747	190	169	84	66	A
140	200	Rp	¾	125	16	738 313 486	3.747	190	169	84	66	A

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>