
Data sheet

valid from: 4/4/26







Profile flange gasket NBR
Metric

Model:

- NBR = Nitrile rubber, hardness approx. 80° Shore
- For all metric GF Flange Adaptors
- Rubber-steel body combined with rubber profile cord ring up to d630
- Rubber-steel body ideal for big dimensions (d710 - d1000)
- Approved acc. to DVGW standard DIN EN 682 for gas
- D corresponds to the centring at the inner diameter of the screw crown

d (mm)	DN (mm)	PN (bar)	NBR Code	Weight (kg)	D (mm)	D1 (mm)	H (mm)	H1 (mm)	Suitable for
20	15	16	**745 440 706**	0.009	51	20	4	3	
25	20	16	**745 440 707**	0.012	61	22	4	3	
32	25	16	**745 440 708**	0.018	71	28	4	3	
40	32	16	**745 440 709**	0.021	82	40	4	3	30 - 40
50	40	16	**745 440 710**	0.029	92	46	4	3	36 - 46
63	50	16	**745 440 711**	0.039	107	58	5	4	48 - 58
75	65	16	**745 440 712**	0.058	127	69	5	4	59 - 69
90	80	16	**745 440 713**	0.063	142	84	5	4	73 - 84
110	100	16	**745 440 714**	0.096	162	104	6	5	94 - 104
125	100	16	**745 440 715**	0.073	162	123	6	5	113 - 123
140	125	16	**745 440 716**	0.128	192	137	6	5	127 - 137
180	150	16	**745 440 717**	0.145	218	160	8	6	150 - 160
200	200	16	**745 440 719**	0.286	273	203	8	6	192 - 203
225	200	16	**745 440 720**	0.183	273	220	6	5	207 - 220
250	250	16	**745 440 721**	0.355	328	252	8	6	238 - 252
280	250	16	**745 440 722**	0.229	328	274	6	5	264 - 274
315	300	16	**745 440 723**	0.419	378	306	8	6	296 - 306
355	350	16	**745 440 724**	0.645	438	355	7	6	340 - 355
400	400	16	**745 440 725**	0.819	489	400	7	6	385 - 400
450	500	10	**745 440 726**	1.885	594	403	10	7	393 - 403
500	500	10	**745 440 727**	1.618	594	447	10	7	437 - 447
560	600	10	**745 440 728**	2.281	695	494	10	7	484 - 494
630	600	10	**745 440 729**	2.000	695	555	10	7	545 - 555
710	710	6	**745 440 733**	0.403	810	712	6	3	562 - 712
800	800	6	**745 440 734**	0.403	917	813	6	3	663 - 813
900	900	6	**745 440 735**	0.403	1017	915	6	3	765 - 915
1000	1000	6	**745 440 736**	0.403	1124	1016	6	3	866 - 1016

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com