



PROGEF Standard Line strainer type 305 With fusion sockets metric

Model:

- Material: PP-H (housing), PP (screen)
- Protects valves, pumps, etc. from becoming soiled
- Easy dismantling for cleaning the screens
- Screen perforation 0.5 mm
- For easy installation and removal
- Overall length according to EN 558

d (mm)	DN (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	EPDM Code	Weight (kg)	FKM Code	Weight (kg)
20	15	10	35	167 305 000	0.209	167 305 049	0.214
25	20	10	65	167 305 050	0.256	167 305 099	0.257
32	25	10	90	167 305 100	0.329	167 305 149	0.327
40	32	10	155	167 305 150	0.579	167 305 199	0.586
50	40	10	225	167 305 200	0.758	167 305 249	0.748
63	50	10	370	167 305 250	1.188	167 305 299	1.185

d (mm)	D (mm)	H (mm)	L (mm)	L2 (mm)	z (mm)	closest inch (inch)
20	52	75	168	130	140	½
25	62	80	192	150	160	¾
32	68	90	206	160	170	1
40	85	110	230	180	190	1 ¼
50	85	125	256	200	210	1 ½
63	102	150	294	230	240	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>