



Multi/Clamp Flange (tapping sleeve) length 600 mm

Model:

- Suitable for all kinds of pipe material. For use on plastic pipes please consult Georg Fischer Waga N.V.
- Double band saddle with flanged outlet
- Full circle construction for optimal pipe support
- To obtain the total product price, please take the price of the tapping sleeve and add the price for the flange outlet
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)
- Water and gas: NBR according to EN 682 (-10°C up to +70°C); potable water: EPDM according to EN 681-1 (-10°C up to +55°C)
- For working pressures in GAS please consult Georg Fischer Waga N.V.
- To choose the correct length of Multi/Clamp check our technical information

Range (mm)	DN (mm)	PN Water (bar)	NBR Code
315 - 335		16.0	315-335L600N
335 - 355		16.0	335-355L600N
- 350		16.0	DN350L600N
- 400		16.0	DN400L600N
- 450		16.0	DN450L600N
- 500		16.0	DN500L600N
- 600		10.0	DN600L600N
- 700			DN700L600N
- 750			DN750L600N
- 800			DN800L600N

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>