



## Multi/Clamp Saddle Studs threaded outlet 1/2"

### Model:

- Saddle with threaded outlet
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)
- Outlet dimension up to 4" available on request
- Lower shell half is without gasket (available on request)
- Other sizes available on request
- Not suitable for the use on plastic pipes
- Water and gas: NBR according to EN 682 (-10°C up to +70°C); potable water: EPDM according to EN 681-1 (-10°C up to +55°C)
- For working pressures in GAS please consult Georg Fischer Waga N.V.

| Range<br>(mm) | max Pressure<br>(bar) | NBR<br>Code        |
|---------------|-----------------------|--------------------|
| 68 - 78       | 16                    | <b>724 201 061</b> |
| 88 - 110      | 16                    | <b>724 201 073</b> |
| 108 - 134     | 16                    | <b>724 201 097</b> |
| 133 - 155     | 16                    | <b>724 201 133</b> |
| 159 - 181     | 16                    | <b>724 201 169</b> |
| 168 - 190     | 16                    | <b>724 201 193</b> |
| 190 - 212     | 16                    | <b>724 201 205</b> |
| 216 - 238     | 16                    | <b>724 201 217</b> |
| 238 - 260     | 16                    | <b>724 201 241</b> |
| 267 - 289     | 16                    | <b>724 201 253</b> |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:  
info.ps@georgfischer.com Internet: <http://www.gfps.com>