





COOL-FIT 4.0 Reducer d32-d225

Model:

- Pre-insulated PE100 SDR11 metric
- Insulation made from GF HE foam
- Outer jacket impact resistant. Color: black
- A: Electrofusion Fitting with integrated sealing lip, for a water and vapour tight sealing
- B: Spigot Fitting with free end (separate electrofusion fitting needed for jointing)
- 738 904 351 and 738 904 368 for direct transitions from COOL-FIT 4.0 to COOL-FIT 2.0



d	d1	D	D1	DN	PN	Code	Weight	D2	L	L1	L2	z	Type
(mm)	(mm)	(mm)	(mm)	(mm)	(bar)		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	
40	32	110	90	32	16	738 903 206	0.250	117	143	40	36	17	A
50	32	110	90	40	16	738 903 209	0.280	117	151	44	36	21	A
50	40	110	110	40	16	738 903 210	0.320	117	149	44	40	15	A
63	32	125	90	50	16	738 903 212	0.217	132	160	48	36	26	A
63	40	125	110	50	16	738 903 213	0.232	132	159	48	40	21	A
63	50	125	110	50	16	738 903 214	0.243	132	159	48	44	17	A
75	63	140	125	65	16	738 903 318	0.264			55	48	170	B
90	63	160	125	80	16	738 903 322	0.387			62	48	190	B
90	75	160	140	80	16	738 903 323	0.416			62	55	189	B
110	63	180	125	100	16	738 903 327	0.566			72	48	204	B
110	75	180	140	100	16	738 903 328	0.577			72	55	205	B
110	90	180	160	100	16	738 903 329	0.644			72	62	205	B
140	63	225	125	125	16	738 903 340	1.118			84	48	225	B
140	75	225	140	125	16	738 903 341	1.202			84	55	237	B
140	90	225	160	125	16	738 903 342	1.251			84	62	238	B
140	110	225	180	125	16	738 903 343	1.271			84	72	233	B
160	63	250	125	150	16	738 903 347	1.298			90	48	244	B
160	90	250	160	150	16	738 903 349	1.323			90	62	244	B
160	110	250	180	150	16	738 903 350	1.362			90	72	242	B
160	140	250	225	150	16	738 903 351	1.845			90	84	257	B
160	140	250	200	150	16	738 904 351	1.664			90	84	257	B
225	63	315	125	200	16	738 903 364	2.960			110	48	295	B
225	90	315	160	200	16	738 903 366	3.018			110	62	295	B
225	110	315	180	200	16	738 903 367	3.079			110	72	295	B
225	140	315	225	200	16	738 903 368	3.443			110	84	296	B
225	140	315	200	200	16	738 904 368	3.172			110	84	296	B
225	160	315	250	200	16	738 903 369	3.550			110	90	279	B

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>