


TP Threaded union G with o-ring PVC-U



d1 (inch)	PN (bar)	EPDM Code	SP	GP	Weight (kg)	E (mm)	Z1 (mm)	Z2 (mm)	L (mm)	F (inch)
3/8	16	RV0B0F160	10	250	0.024	34.0	5.6	13.6	11	3/4
1/2	16	RV0B0F200	10	150	0.040	42.0	4.0	11.0	15	1
3/4	16	RV0B0F250	10	100	0.065	52.0	5.7	12.7	16	1 1/4
1	16	RV0B0F320	10	60	0.095	59.0	5.9	12.9	19	1 1/2
1 1/4	16	RV0B0F400	1	90	0.155	72.0	7.6	16.6	21	2
1 1/2	16	RV0B0F500	1	60	0.230	79.0	12.6	23.6	21	2 1/4
2	16	RV0B0F630	1	36	0.400	96.0	15.3	30.3	26	2 3/4
2 1/2	10	RV0B0F750	1	20	0.583	119.0	16.8	31.8	30	3 1/2
3	10	RV0B0F900	1	15	0.842	134.0	22.7	35.7	33	4
4	10	RV0B0F910	1	18	1.229	163.0	26.7	39.7	39	5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>