




ELGEF Plus Transition elbow 90° PE/brass
d32-63mm / SDR11 /Female thread Rp

- 10 bar Gas / 16 bar Water
- With integral pipe fixation
- 4 mm pin connectors
- Limited path fusion indicators
- Supplied as a kit



d	Thread Type	Size	DN	PN	Code	Weight
(mm)		(inch)	(mm)	(bar)		(kg)
32	Rp	1	25	16	720 100 258	0.359
40	Rp	1 1/4	32	16	720 100 259	0.525
50	Rp	1 1/2	40	16	720 100 260	0.825
63	Rp	1	50	16	720 100 281	1.420
63	Rp	1 1/4	50	16	720 100 282	1.391
63	Rp	1 1/2	50	16	720 100 283	1.305
63	Rp	2	50	16	720 100 261	1.165

d	Do	L1	P1	SLW	Suitable for
(mm)	(mm)	(mm)	(mm)	(mm)	
32	44	89	34	40	Pipe SDR 9-11
40	54	100	38	50	Pipe SDR 9-11
50	66	109	42	60	Pipe SDR 9-11
63	81	123	46	70	Pipe SDR 9-11
63	81	123	46	70	Pipe SDR 9-17.6
63	81	123	46	70	Pipe SDR 9-17.6
63	81	123	46	70	Pipe SDR 9-17.6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
 info.ps@georgfischer.com Internet: <http://www.gfps.com>