


Data sheet

valid from: 5/5/25



Elbow 90° ABS metric / BS

- >d225 - maximum operating temperature: +40°C

d	Size	PN	Code	SP	Weight	D	L	z	closest
(mm)	(inch)	(bar)			(kg)	(mm)	(mm)	(mm)	inch
									(inch)
20		16	729 100 106	10	0.010	26	27	11	½
25		16	729 100 107	10	0.018	31	33	14	¾
32		10	729 100 108	10	0.033	40	39	17	1
40		10	729 100 109	10	0.055	49	47	21	1 ¼
50		10	729 100 110	10	0.098	61	57	26	1 ½
63		10	729 100 111	10	0.186	76	72	33	2
* 75	2 ½	10	729 100 112	5	0.300	90	84	40	2 ½
90		10	729 100 113	5	0.432	110	97	46	3
110		10	729 100 114	3	0.769	136	116	55	4
* 140	5	10	729 100 116	8	1.258	162	146	70	5
160		10	729 100 117	1	2.209	185	166	80	6
200		10	729 100 119	1	3.372	225	207	101	8
	½	15	729 101 106	10	0.017	28	30	13	
	¾	15	729 101 107	10	0.027	34	37	16	
	1	15	729 101 108	10	0.033	40	42	19	
	1 ¼	15	729 101 109	10	0.060	52	51	22	
	1 ½	15	729 101 110	10	0.090	58	56	26	
	2	15	729 101 111	10	0.162	73	68	32	
	3	15	729 101 113	5	0.444	107	97	46	
	4	15	729 101 115	2	1.008	137	122	59	

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>