




COOL-FIT 4.0 Transition Tee90° PE/stainless steel With female thread Rp

Model:

- Pre-insulated PE100 SDR11 metric
- Stainless steel 1.4404 / 316L with female thread Rp
- Insulation made from GF HE foam
- Impact resistant. Color: black
- Electrofusion Fitting with integrated sealing lip, for a water and vapour tight sealing

d	D	DN	Thread	Size	PN	Code	Weight	H	L	L1	z
(mm)	(mm)	(mm)		(inch)	(bar)		(kg)	(mm)	(mm)	(mm)	(mm)
63	125	50	Rp	2	16	738 943 061	1.700	222	103	48	30
75	140	65	Rp	2	16	738 943 062	2.150	226	116	55	36
90	160	80	Rp	2	16	738 943 063	2.530	241	130	62	43
110	180	100	Rp	2	16	738 943 064	3.650	251	154	72	57
160	250	150	Rp	2	16	738 943 067	5.380	289	192	90	77
225	315	200	Rp	2	16	738 943 070	18.100	446	355	110	220
40	110	32	Rp	1	16	738 943 159	0.490	173	87	40	22
50	110	40	Rp	1	16	738 943 160	0.575	173	94	44	25
63	125	50	Rp	1	16	738 943 161	0.747	186	103	48	30
75	140	65	Rp	1	16	738 943 162	1.233	193	116	55	36
90	160	80	Rp	1	16	738 943 163	1.633	205	130	62	43
110	180	100	Rp	1	16	738 943 164	2.733	215	154	72	57
160	250	150	Rp	1	16	738 943 167	4.483	253	192	90	77
225	315	200	Rp	1	16	738 943 170	17.100	444	355	110	220

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:

info.ps@georgfischer.com Internet: <http://www.gfps.com>