


**ABS Ball valve type 127**  
**100-230V**  
**With manual emergency override**  
**With solvent cement sockets ABS ISO**

**Model:**


- IP68 Rating
- Factory set control range 90°<
- Heating element, position feedback (Open/Close)
- Integrated stainless steel mounting inserts

**Option:**


- Other valve and actuator configurations available
- Optional accessories: Fail-safe return unit



| d    | DN   | Size   | PN    | kv-value            | EPDM               | Weight |
|------|------|--------|-------|---------------------|--------------------|--------|
| (mm) | (mm) | (inch) | (bar) | ( $\Delta p=1$ bar) | Code               | (kg)   |
|      |      |        |       | (l/min)             |                    |        |
| 16   | 10   | 3/8    | 10    | 70                  | <b>199 127 082</b> | 2.072  |
| 20   | 15   | 1/2    | 10    | 185                 | <b>199 127 083</b> | 2.072  |
| 25   | 20   | 3/4    | 10    | 350                 | <b>199 127 084</b> | 2.189  |
| 32   | 25   | 1      | 10    | 700                 | <b>199 127 085</b> | 2.261  |
| 40   | 32   | 1 1/4  | 10    | 1000                | <b>199 127 086</b> | 2.465  |
| 50   | 40   | 1 1/2  | 10    | 1600                | <b>199 127 087</b> | 2.648  |
| 63   | 50   | 2      | 10    | 3100                | <b>199 127 088</b> | 3.222  |



| d    | Actuator | B3   | DE1  | E    | G    | H    | H1   | H4   | L    | L1   | Lz   | M    | M1   | M2   | z    |
|------|----------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| (mm) |          | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) |
| 16   | EA15     | 25   | 50   | 122  | M6   | 197  | 27   | 12   | 92   | 33   | 28   | 161  | 77   | 83   | 64   |
| 20   | EA15     | 25   | 50   | 122  | M6   | 197  | 27   | 12   | 95   | 33   | 28   | 161  | 77   | 83   | 64   |
| 25   | EA15     | 25   | 58   | 122  | M6   | 201  | 30   | 12   | 110  | 33   | 33   | 161  | 77   | 83   | 72   |
| 32   | EA15     | 25   | 68   | 122  | M6   | 207  | 36   | 12   | 123  | 33   | 36   | 161  | 77   | 83   | 79   |
| 40   | EA15     | 45   | 84   | 122  | M8   | 213  | 44   | 15   | 146  | 33   | 43   | 161  | 77   | 83   | 94   |
| 50   | EA15     | 45   | 97   | 122  | M8   | 219  | 51   | 15   | 157  | 33   | 45   | 161  | 77   | 83   | 95   |
| 63   | EA15     | 45   | 124  | 122  | M8   | 234  | 64   | 15   | 183  | 33   | 51   | 161  | 77   | 83   | 107  |



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:  
 info.ps@georgfischer.com Internet: <http://www.gfps.com>