



PROGEF Standard Outlet flange adaptor SDR11/PN10

Model:

- Material: PP-H
- Conventional butt-welding according to DVS 2207
- To wafer check valves type 369

Attention:

- In conjunction with Outlet flange adaptors, **flange rings for socket systems** must be used.

d	DN	PN	Code	Weight	L	L1	L2	D	D1	D2	r	e
(mm)	(mm)	(bar)		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
40	32	10	727 808 034	0.172	64	30	11	80	37	50	3	3.7
50	40	10	727 808 035	0.096	67	30	12	90	43	61	3	4.6
63	50	10	727 808 036	0.157	74	30	14	105	54	76	4	5.8
75	65	10	727 808 037	0.223	78	30	16	125	70	90	4	6.8
90	80	10	727 808 038	0.325	87	35	17	140	82	108	4	8.2
110	100	10	727 808 039	0.475	102	41	18	160	105	131	4	10.0
140	125	10	727 808 041	0.899	124	47	25	190	130	165	4	12.7
160	150	10	727 808 042	1.246	149	52	25	215	158	188	4	14.6
225	200	10	727 808 045	2.638	180	55	32	270	206	248	4	20.5
280	250	10	727 808 047	4.088	240	63	35	325	259	308	4	25.4
315	300	10	727 808 048	4.960	272	66	35	375	308	346	4	28.6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>