





PROGEF Standard Diaphragm valve type 514
With butt fusion spigots SDR11 metric

Model:

- Material: PP-H
- Double flow rate compared to predecessor
- One housing nut replaces four screws
- Handwheel with built-in locking mechanism
- For easy installation and removal
- Short overall length

Option:

- Individual configuration of the valve
- Self adjusting multifunctional module with integrated limit switches

d	DN	Size	PN	kv-value
(mm)	(mm)	(inch)	(bar)	($\Delta p=1$ bar)
				(l/min)
20	15	½	10	125
25	20	¾	10	271
32	25	1	10	481
40	32	1 ¼	10	759
50	40	1 ½	10	1263
63	50	2	10	1728

d	NBR	EPDM	PTFE/ EPDM*	FKM	Weight
(mm)	Code	Code	Code	Code	(kg)
20	167 514 102	167 514 112	167 514 132	167 514 162	0.390
25	167 514 103	167 514 113	167 514 133	167 514 163	0.520
32	167 514 104	167 514 114	167 514 134	167 514 164	0.625
40	167 514 105	167 514 115	167 514 135	167 514 165	1.340
50	167 514 106	167 514 116	167 514 136	167 514 166	2.360
63	167 514 107	167 514 117	167 514 137	167 514 167	3.090

d	D	D2	D3	H	H1	H2	L	L2	M	e	Lift = Hx	closest inch
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		(mm)	(mm)	(inch)
20	65	65	48	73	14	12	196	25	M6	1.9	7	½
25	80	65	58	81	18	12	221	25	M6	2.3	10	¾
32	88	87	65	107	22	12	234	25	M6	2.9	13	1
40	101	87	79	115	26	15	260	45	M8	3.7	15	1 ¼
50	117	135	91	148	32	15	284	45	M8	4.6	19	1 ½
63	144	135	111	166	39	15	321	45	M8	5.8	25	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
 info.ps@georgfischer.com Internet: <http://www.gfps.com>