


TP Threaded central offtake tee Rp PVC-U



d (mm)	d (inch)	Rp (inch)	PN (bar)	Code	SP	GP	Weight (kg)	L2 (mm)	Z2 (mm)	E (mm)	Z1 (mm)	L1 (mm)
16		3/8	16	RV0TIP16A	10	280	0.017	11.4	11.6	23	9	14
20		1/2	16	RV0TIP20B	10	150	0.028	15.0	12.0	28	11	16
25		3/4	16	RV0TIP25C	10	100	0.044	16.3	16.7	34	14	19
32		1	16	RV0TIP32D	10	130	0.073	19.1	19.9	42	17	22
40		1 1/4	16	RV0TIP40E	1	90	0.125	21.4	25.6	51	21	26
50		1 1/2	16	RV0TIP50F	1	50	0.198	21.4	35.6	61	26	31
63		2	16	RV0TIP63G	1	25	0.337	25.7	45.3	75	33	38
75	2 1/2	2 1/2	16	RV0TIP75H	1	35	0.537	30.2	52.8	89	39	44
90		3	16	RV0TIP90I	1	24	0.825	33.3	64.7	106	47	51
110		4	16	RV0TIP91L	1	14	1.395	39.3	78.7	129	57	61

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>