




ABS Angle seat check valve type 303
With solvent cement spigots metric

Model:

- For horizontal or vertical installation
- Leakproof from: EPDM 2m, FKM 3m water column
- Specific gravity of piston approx. 2 kg/dm³
- Overall length EN 558



d	DN	PN	kv-value	EPDM	SP	Weight	D	H	L	L1	L2	closest
(mm)	(mm)	(bar)	($\Delta p=1$ bar)	Code		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	inch
			(l/min)									(inch)
20	15	10	95	169 303 006	1	0.092	43	65	124	130	28	½
25	20	10	180	169 303 007	1	0.133	47	75	144	150	37	¾
32	25	10	327	169 303 008	1	0.219	56	90	154	160	37	1
40	32	10	484	169 303 009	1	0.348	64	102	174	180	44	1 ¼
50	40	10	725	169 303 010	1	0.615	82	123	194	200	48	1 ½
63	50	10	1130	169 303 011	1	1.059	95	144	224	230	60	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>