Data sheet

valid from: 4/5/26

Form I



Form II



Form III



241
Reducing bush, ISO/EN N4

Forms I, II, III are available only as marked under column "Form", Form I can also be supplied with continuous internal thread (=241D).
ST ... these types of fittings are made from steel (galvanised finish = electroplated) and not suitable for drinking water installations.

	d1 (inch)	d2 (inch)	Form	Black Code	Galvanised Code	SP	GP	a (mm)	b (mm)	z (mm)	s (mm)
EN *-	¼	⅛	I	**770 241 115**	**770 241 215**	10		20		13	17
EN *-	⅜	⅛	I	**770 241 116**	**770 241 216**	10		20		13	19
EN *-	⅜	¼	I	**770 241 117**	**770 241 217**	10		20		10	19
EN *-	½	⅛	II	**770 241 118**	**770 241 218**	10		24		17	23
EN *-	½	¼	II	**770 241 119**	**770 241 219**	10		24		14	23
EN *-	½	⅜	I	**770 241 120**	**770 241 220**	10		24		14	23
EN *-	¾	¼	II	**770 241 121**	**770 241 221**	10		26		16	30
EN *-	¾	⅜	II	**770 241 122**	**770 241 222**	10		27		16	30
EN *-	¾	½	I	**770 241 123**	**770 241 223**	10		26		13	30
EN *-	1	¼	II	**770 241 124**	**770 241 224**	10		29		19	36
EN *-	1	⅜	II	**770 241 125**	**770 241 225**	10		29		19	36
EN *-	1	½	II	**770 241 126**	**770 241 226**	10		29		16	36
EN *-	1	¾	I	**770 241 127**	**770 241 227**	10		30		15	36
EN *-	1 ¼	⅜	II	**770 241 128**	**770 241 228**	40		31		21	46
EN *-	1 ¼	½	II	**770 241 129**	**770 241 229**	100		31		18	46
EN *-	1 ¼	¾	II	**770 241 130**	**770 241 230**	100		31		16	46
EN *-	1 ¼	1	II	**770 241 131**	**770 241 231**	100		31		14	46
EN *-	1 ½	⅜	II	**770 241 132**	**770 241 232**	80		31		21	50
EN *-	1 ½	½	II	**770 241 133**	**770 241 233**	80		31		18	50
EN *-	1 ½	¾	II	**770 241 134**	**770 241 234**	80		31		16	50
EN *-	1 ½	1	II	**770 241 135**	**770 241 235**	60		31		14	50
EN *-	1 ½	1 ¼	I	**770 241 136**	**770 241 236**	60		33		12	50
EN *-	2 ½	½	III	**770 241 137**	**770 241 237**	30		35	48	35	65
EN *-	2	¾	III	**770 241 138**	**770 241 238**	30		35	49	34	65
EN *-	2	1	II	**770 241 139**	**770 241 239**	30		37		20	65
EN *-	2	1 ¼	II	**770 241 140**	**770 241 240**	30		37		18	65
EN *-	2 ½	1	III	**770 241 142**	**770 241 242**	20		44	54	37	80
EN *-	2	1 ½	II	**770 241 141**	**770 241 241**	30		37		18	65
EN *-	2 ½	1 ¼	III	**770 241 143**	**770 241 243**	20		40	54	37	80
EN *-	2 ½	1 ½	II	**770 241 144**	**770 241 244**	20		42		23	80
EN *-	2 ½	2	II	**770 241 145**	**770 241 245**	20		40		16	80
EN *-	3	1	III	**770 241 146**	**770 241 246**	10		44	59	42	95
EN *-	3	1 ¼	III	**770 241 147**	**770 241 247**	10		44	59	40	95
EN *-	3	1 ½	III	**770 241 148**	**770 241 248**	10		44	59	40	95
EN *-	3	2	II	**770 241 149**	**770 241 249**	10		44		20	95
EN *-	3	2 ½	II	**770 241 150**	**770 241 250**	10		44		17	96
EN *-	4	2	III	**770 241 151**	**770 241 251**	6		51	69	45	120
EN *-	4	2 ½	III	**770 241 152**	**770 241 252**	6		51	69	42	120
EN *-	4	3	II	**770 241 153**	**770 241 253**	6		53		23	120

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com