




ABS Ball Valve type 546 Pro With threaded sockets ABS ISO Rp

Model:


- Lockable lever as standard
- Ball seat PTFE
- Integrated stainless steel mounting inserts
- z-dimension, valve end and union nut are compatible with type 546 (1st Generation)

Option:

- Interface module for position feedback sensor with LED (PNP, NPN and NAMUR)
- Manual spring return lever "Dead man" (DN10-25)
- Pneumatic or electric actuators from GF
- Individual configuration of valves possible



d	DN	Size	PN	kv-value	EPDM	SP	Weight
(mm)	(mm)	(inch)	(bar)	($\Delta p=1$ bar)	Code		(kg)
				(l/min)			
16	10	3/8	10	70	169 546 021	1	0.112
20	15	1/2	10	185	169 546 022	1	0.114
25	20	3/4	10	350	169 546 023	1	0.178
32	25	1	10	700	169 546 024	1	0.258
40	32	1 1/4	10	1000	169 546 025	1	0.457
50	40	1 1/2	10	1600	169 546 026	1	0.642
63	50	2	10	3100	169 546 027	1	1.175



d	B3	DE1	G	H	H1	H4	L	Lz	M	M1	M2	z
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
16	25	50	M6	60.5	27	12	95	28	82	35	47	69
20	25	50	M6	60.5	27	12	100	28	82	35	47	67
25	25	58	M6	74.0	30	12	114	33	106	44	62	78
32	25	68	M6	80.0	36	12	127	36	106	44	62	85
40	45	84	M8	95.0	44	15	146	43	131	57	74	100
50	45	97	M8	101.5	51	15	152	45	131	57	74	106
63	45	124	M8	116.5	64	15	177	51	152	66	86	121

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>