



PROGEF Standard Lug-style end installation butterfly valve type 578
With gear box
Flange standard metric

Model:




- Housing material: PP-GF30 with SS316 lug-inserts
- Connecting dimension: ISO 7005 PN10, EN 1092 PN10, DIN 2501 PN10
- Overall length according to EN 558, ISO 5752 (DN50 - 200 line 25, DN250 - 300 line 10)

Option:

- Optional accessory: Valve-Integrated position feedback with limit switches (limit switches have to be ordered separately)

Note:

For some material combination (e.g. DN300 valves with PE/PP pipes) special flange adapters are needed. Please check the "Perfect flange connection tool" on www.gfps.com



d (mm)	Size (inch)	DN (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	EPDM Code	Weight (kg)	FKM Code	Weight (kg)
63	2	50	10	740	167 578 042	3.447	167 578 062	3.447
75	2 1/2	65	10	1500	167 578 043	3.585	167 578 063	3.585
90	3	80	10	2400	167 578 044	3.929	167 578 064	3.929
110	4	100	10	3800	167 578 045	4.834	167 578 065	4.834
140	5	125	10	8600	167 578 046	6.348	167 578 066	6.348
160	6	150	10	11400	167 578 047	8.109	167 578 067	8.109
225	8	200	10	19900	167 578 048	9.353	167 578 068	9.353
280	10	250	8	34000	167 578 049	21.210	167 578 069	21.210
315	12	300	8	50000	167 578 050	27.746	167 578 070	27.746

d (mm)	Hmax (mm)	Lmax (mm)	Wmax (mm)	U (mm)	V (mm)	H4 (mm)	V1 (mm)	Lg (mm)	D2 (mm)	Q1 (mm)	Q2 (mm)	d2 (mm)	k (mm)	Y (mm)
63	319.4	169.1	263.5	90	133.3	23	78.8	44.7	160	40		M16	125	61.2
75	332.3	169.1	272.0	90	139.9	23	85.1	45.7	180	54	35	M16	145	61.2
90	344.1	169.1	286.0	90	145.6	23	91.2	48.7	195	67	50	M16	160	61.2
110	380.8	169.1	301.0	90	166.0	23	107.5	55.6	226	88	74	M16	180	61.2
140	410.0	169.1	317.0	90	180.0	23	122.7	63.5	258	113	97	M16	210	61.2
160	430.8	169.1	321.0	90	189.0	23	134.5	71.5	284	139	123	M20	240	61.2
225	479.3	169.1	360.0	90	210.5	23	161.5	72.5	341	178	169	M20	295	61.2
280	615.6	212.6	440.0	125	264.4	23	206.9	113.2	412	210	207	M20	350	68.4
315	665.0	212.6	510.0	125	285.2	23	235.5	114.6	482	256	253	M20	400	68.4

d (mm)	E (mm)	Y1 (mm)	M (mm)	LV (mm)	LB (mm)
63	80		160	112.3	129.5
75	80		160	112.3	129.5
90	80		160	112.3	129.5
110	80		160	112.3	129.5
140	80		160	112.3	129.5
160	80		160	112.3	129.5
225	80		160	112.3	129.5
280	100	17.0	160	130.0	134.0
315	100	17.0	160	130.0	134.0

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Data sheet

valid from: 8/26/26



Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>