
Data sheet

valid from: 10/13/26





Angle seat check valve type 303 PVC-U
With solvent cement spigots metric

Model:

- For horizontal or vertical installation
- Leakproof from: EPDM 2m, FKM 3m water column
- Specific gravity of piston approx. 2 kg/dm³
- Overall length EN 558

d (mm)	DN (mm)	PN (bar)	kv-value (Δp=1 bar) (l/min)	EPDM Code	SP	Weight (kg)	FKM Code	SP	Weight (kg)
16	10	10	41	**161 303 005**	1	0.075	**161 303 030**	1	0.094
20	15	10	95	**161 303 006**	1	0.113	**161 303 031**	1	0.132
25	20	10	180	**161 303 007**	1	0.170	**161 303 032**	1	0.172
32	25	10	327	**161 303 008**	1	0.288	**161 303 033**	1	0.290
40	32	10	484	**161 303 009**	1	0.444	**161 303 034**	1	0.448
50	40	10	725	**161 303 010**	1	0.791	**161 303 035**	1	0.798
63	50	10	1130	**161 303 011**	1	1.345	**161 303 036**	1	1.345
75	65	10	1700	**161 303 012**	1	2.483	**161 303 037**	1	2.499
90	80	10	2500	**161 303 013**	1	3.514	**161 303 038**	1	3.540

d (mm)	D (mm)	H (mm)	L (mm)	L1 (mm)	L2 (mm)	closest inch (inch)
16	39	58	114	120	24	⅜
20	43	65	124	130	28	½
25	47	75	144	150	37	¾
32	56	90	154	160	37	1
40	64	102	174	180	44	1 ¼
50	82	123	194	200	48	1 ½
63	95	144	224	230	60	2
75	92	186	284	290	74	2 ½
90	104	204	300	310	85	3

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: http://www.gfps.com