



ecoFIT Adaptor socket PE100
d20-63mm / SDR11 / Female thread Rp

Model:

- With butt fusion spigot **SDR11** and BSP parallel female thread Rp, reinforced
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Do not use thread sealing pastes that are harmful to PE
- Install with low mechanical stress and avoid large cyclic temperature changes

d	Thread Type	Size	DN	PN	SDR	FM	Code	Weight	Lmax	s1	SLW	Bm1
(mm)		(inch)	(mm)	(bar)				(kg)	(mm)	(mm)	(mm)	(mm)
20	Rp	½	15	16	11	IR	753 910 266	0.018	49	1.9	32	23
32	Rp	1	25	16	11	IR	753 910 268	0.038	55	3.0	46	23
25	Rp	¾	20	16	11	IR	753 910 267	0.022	51	2.3	36	23
40	Rp	1 ¼	32	16	11	IR	753 910 269	0.068	57	3.7	55	23
50	Rp	1 ½	40	16	11	IR	753 910 270	0.083	60	4.6	64	23
63	Rp	2	50	16	11	IR	753 910 271	0.134	62	5.8	80	23

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>