




ecoFIT Ventilating and bleed valve Type 591
With butt fusion spigots long
PE100 SDR11 metric

Model:

- Material: PVC-U/PE
- With protection cap up to DN50 made of PP-GF, DN65-100 made of POM
- Floater made of PP-H
- Designed for easy installation and removal
- Compact installation length



d	SDR	DN	PN	EPDM	FKM	D	L	L2	t	e	closest inch
(mm)		(mm)	(bar)	Code	Code	(mm)	(mm)	(mm)	(mm)	(mm)	(inch)
20	11	15	16	161 591 121	161 591 130	50	174	56	69	2.25	1/2
25	11	20	16	161 591 122	161 591 131	58	195	65	76	2.30	3/4
32	11	25	16	161 591 123	161 591 132	68	207	71	76	2.90	1
40	11	32	16	161 591 124	161 591 133	84	230	85	82	3.70	1 1/4
50	11	40	16	161 591 125	161 591 134	97	254	89	91	4.60	1 1/2
63	11	50	16	161 591 126	161 591 135	124	298	101	110	5.80	2
75	11	65	16	161 591 127	161 591 136	166	358	136	125	6.80	2 1/2
90	11	80	16	161 591 128	161 591 137	200	387	141	140	8.20	3
110	11	100	16	161 591 129	161 591 138	238	441	164	160	10.00	4

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
 info.ps@georgfischer.com Internet: <http://www.gfps.com>