



Installation fitting type 310 PVC-C For socket systems metric

Range of use:

- Compatible Signet flow sensors: type 2551, 2537, 515, 8510, 2536, 8512
- Compatible Signet pH/ORP sensors: type 2724, 2725, 2726, 2734, 2736, 2735

Attention:

- sensor length depends on installation fitting

Model:

- Threaded outlet 1 1/4" NPSM
- Body and union nut PVDF
- Union end with solvent cement socket PVC-C

d (mm)	DN (mm)	PN (bar)	EPDM Code	SP	Weight (kg)	FKM Code	SP	Weight (kg)
20	15	16	723 310 006	1	0.250	723 310 036	1	0.250
25	20	16	723 310 007	1	0.355	723 310 037	1	0.355
32	25	16	723 310 008	1	0.427	723 310 038	1	0.427
40	32	16	723 310 009	1	0.700	723 310 039	1	0.700
50	40	16	723 310 010	1	0.850	723 310 040	1	0.850
63	50	16	723 310 011	1	1.182	723 310 041	1	1.182

d (mm)	DN (mm)	D (mm)	L (mm)	L1 (mm)	H (mm)	z (mm)	Sensor Type
20	15	45	132	90	76	49	X0 (DN15 – DN100, 1/2" to 4")
25	20	55	148	100	78	53	X0 (DN15 – DN100, 1/2" to 4")
32	25	62	164	110	81	58	X0 (DN15 – DN100, 1/2" to 4")
40	32	75	172	110	85	58	X0 (DN15 – DN100, 1/2" to 4")
50	40	84	188	120	89	63	X0 (DN15 – DN100, 1/2" to 4")
63	50	101	212	130	95	68	X0 (DN15 – DN100, 1/2" to 4")

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>