


PVC Branch 45° and 87° SN8 (SDR 34)



Material	PVC-U
Ring stiffness	SN8 (SDR 34)
Application	Non-pressure underground sewage and rainwater drainage outside buildings
Joining	Socket with EPDM sealing ring

Code	D (mm)	α (°)	Z1 (mm)	Z2 (mm)	Z3 (mm)	L (mm)
FVE0394	125/110	45	18	144	141	279
FVE0396	125/125	45	29	152	152	301
FVE0399	160/160	45	37	194	194	370
FVE0402	200/160	45	19	221	214	395
FVE0406	250/160	45	45	285	285	530
FVE0408	250/200	45	45	290	285	530
FVE0410	250/250	45	45	315	285	610
FVE0414	315/160	45	60	325	325	320
FVE0415	315/200	45	60	325	325	320
FVE0416	315/250	45	170	585	585	470
COA301545	315/160	45	20	330	330	610
FVE0420	400/160	45	-70	465	440	800
FVE0421	400/200	45	-95	510	465	800
FVE0422	400/250	45	345	640	725	1500
FVE0423	400/315	45	345	530	725	1500
FVE0425	500/160	45	550	535	480	1500
FVE0426	500/200	45	520	580	510	1500
FVE0427	500/250	45	280	710	750	1500
FVE0428	500/315	45	280	595	750	1500
FVE0429	500/400	45	280	670	750	1500
FVE0430	630/160	45	195	670	785	1500
FVE0431	630/250	45	195	795	785	1500
FVE0432	630/315	45	195	680	785	1500
FVE0433	710/160	45	90	740	760	1500
FVE0434	710/250	45	90	850	760	1500
FVE0435	710/315	45	90	735	760	1500
FVE0436	800/200	45	45	835	795	1500
FVE0437	800/250	45	45	885	795	1500
FVE0438	800/500	45	295	900	1045	2000

Dimensions as published by the manufacturer; symbols refer to the drawing above.