



PROGEF Standard Ball Valve type 546 Pro
With butt fusion spigots SDR17.6 ISO

Model:

- Lockable lever as standard
- Ball seat PTFE
- Integrated stainless steel mounting inserts
- Z-dimension, valve end and union nut **are compatible** with type 546 (1st Generation)

Option:

- Interface module for position feedback sensor with LED (PNP, NPN and NAMUR)
- Manual spring return lever "Dead man" (DN10-25)
- Pneumatic or electric actuators from GF
- Individual configuration of valves possible



d	DN	Size	PN	kv-value	EPDM	SP	Weight	FKM	SP	Weight
(mm)	(mm)	(inch)	(bar)	($\Delta p=1$ bar)	Code		(kg)	Code		(kg)
				(l/min)						
40	32	1 ¼	10	1000	167 546 065	1	0.450		1	0.450
50	40	1 ½	10	1600	167 546 066	1	0.635	167 546 076	1	0.635
63	50	2	10	3100	167 546 067	1	1.159	167 546 077	1	1.200
75	65	2 ½	10	5000	167 546 068	1	2.575	167 546 078	1	3.387
90	80	3	10	7000	167 546 069	1	4.731	167 546 079	1	5.500
110	100	4	10	11000	167 546 070	1	8.600	167 546 080	1	8.600

d	B3	DE1	G	H	H1	H4	L	Lz	M	M1	M2	s1
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
40	45	84	M8	95.0	44	15	171	43	131	57	74	
50	45	97	M8	101.5	51	15	191	45	131	57	74	2.9
63	45	124	M8	116.5	64	15	220	51	152	66	86	3.6
75	70	166	M8	169.0	85	15	266	68	270	64	205	4.6
90	70	200	M8	180.0	105	15	264	71	270	64	205	5.5
110	120	238	M12	194.0	123	22	301	82	326	71	255	6.7

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>