



PROGEF Standard Outlet flange adaptor SDR17.6/PN6

Model:

- Material: PP-H
- Conventional butt-welding according to DVS 2207
- To wafer check valves type 369

Attention:

- In conjunction with Outlet flange adaptors, **flange rings for socket systems** must be used.

d	DN	PN	Code	Weight	L	L1	L2	D	D1	D2	r	e
(mm)	(mm)	(bar)		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
40	32	6	727 808 009	0.048	64	30	11	80	37	50	3	2.3
50	40	6	727 808 010	0.091	67	30	12	90	43	61	3	2.9
63	50	6	727 808 011	0.096	74	30	14	105	54	76	4	3.6
75	65	6	727 808 012	0.170	78	30	16	125	70	90	4	4.3
90	80	6	727 808 013	0.260	87	35	17	140	82	108	4	5.1
110	100	6	727 808 014	0.429	102	41	18	160	105	131	4	6.3
140	125	6	727 808 016	0.808	124	47	18	190	130	165	4	8.0
160	150	6	727 808 017	1.107	149	52	18	215	158	188	4	9.1
225	200	6	727 808 020	2.324	180	55	24	270	206	248	4	12.7
280	250	6	727 808 022	3.563	240	63	25	325	259	308	4	15.9
315	300	6	727 808 023	2.450	272	66	25	375	308	346	4	17.9

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>